

LOUISVILLE INTL—STANDIFORD FLD (SDF) 4 S UTC-5(-4DT) N38°10.45' W85°44.19'

ST LOUIS

501 B S4 FUEL 100LL, JET A OX 4 LRA Class I, ARFF Index C NOTAM FILE SDF

H-5E, 10F, L-27E

RWY 17R-35L: H11890X150 (CONC-GRVD) S-75, D-207, 2D-360, 2D/2D2-850

IAP, AD

PCN 70 R/C/W/T HIRL CL

RWY 17R: MALS.R. TDZL. PAPI(P4L)—GA 3.0° TCH 75'.

Thld dsplcd 850'.

RWY 35L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 75'. Thld dsplcd 1040'.

RWY 17L-35R: H8579X150 (CONC-GRVD) S-75, D-207, 2D-360,

2D/2D2-850 PCN 70 R/C/W/T HIRL CL

RWY 17L: MALS.R. TDZL PAPI(P4L)—GA 3.0° TCH 75'.

Thld dsplcd 329'. 0.3% down.

RWY 35R: ALSF2. TDZL PAPI(P4R)—GA 3.0° TCH 75'.

Thld dsplcd 450'. 0.3% up.

RWY 11-29: H7250X150 (CONC-WC) S-75, D-170, 2D-360,

2D/2D2-850 PCN 59 R/C/W/T HIRL

RWY 11: Bldg. RWY 29: MALS.R.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 17L: TORA-8579 TODA-8579 ASDA-8129 LDA-7800

RWY 17R: TORA-11095 TODA-11095 ASDA-11095 LDA-10000

RWY 35L: TORA-11290 TODA-11290 ASDA-11290 LDA-10000

RWY 35R: TORA-8579 TODA-8579 ASDA-8250 LDA-7800

AIRPORT REMARKS: Attended continuously. Continuous construction on arpt, be alert for frequent rwy and twy closures. Birds on and in/ov arpt. ASDE-X Surveillance System in use: Pilots should opr transponders with Mode C on all twys and rwys. Taxi in position and hold waiver in effect from 0830Z until SR at the intersection of Rwy 17R at Twy B and at the intersection of Rwy 35L at Twy B. These rwys will be used for departures only when exercising the provisions of this waiver. Std dep point on Rwy 17R is at Twy B. Pilots must req use of Rwy 17R extension. Declared distance for tkf at Twy B ASDA/TORA/TODA 10,245'. Std dep point on Rwy 35L is at Twy B. Pilots must req use of Rwy 35L extension. Declared distance for tkf at Twy B ASDA/TORA/TODA 10,250'. Rwy 17L RVR avbl touchdown, midpoint and rollout. Rwy 17R RVR avbl touchdown, midpoint and rollout. Rwy 35L RVR avbl touchdown, midpoint, rollout. Rwy 35R RVR avbl touchdown, midpoint and rollout. Flight Notification Service (ADCUS) avbl.

WEATHER DATA SOURCES: ASOS (502) 367-1492. LLWAS.

COMMUNICATIONS: D-ATIS 118.725 UNICOM 122.95

Ⓡ APP CON 134.15 132.075(E) 123.675(W)

Ⓡ DEP CON 132.075(E) 123.675(W)

TOWER 124.2 GND CON 121.7 CLNC DEL 126.1

AIRSPACE: CLASS C svc continuous ctc APP CON

RADIO AIDS TO NAVIGATION: NOTAM FILE LOU.

(H) VORTAC 114.8 IU Chan 95 N38°06.21' W85°34.65' 298° 8.6 NM to fld. 720/01E.

LAANG NDB (LOM) 414 LK N38°08.69' W85°38.00' 293° 5.2 NM to fld. NOTAM FILE SDF.


ILS/DME 110.55 I-JJM Chan 42(Y) Rwy 35R. Class IIIE.

ILS 109.1 I-LKS Rwy 29. LOM LAANG NDB. LOC only. (LOC BC unusable).

ILS/DME 109.35 I-RLI Chan 30(Y) Rwy 35L. Class IIIE.

ILS/DME 111.95 I-PKI Chan 56(Y) Rwy 17L. Class IE.

ILS/DME 110.3 I-SNU Chan 40 Rwy 17R.



MADISON (See RICHMOND)